

Supernova Power Unit

Carni • Sandwiches • Bevande • Latticini • Prodotti freschi
Meat • Sandwiches • Drinks • Dairy • Fresh Products

H 205

P 78

L 94 • 125 • 188 • 250

Installazione

Plug-in

Temperatura di esercizio

0 / +2 °C

Refrigerante

R290

Refrigerazione

Ventilata
Power Unit

Classe di prodotto

M0

Classe climatica

3

Sbrinamento

Fermata compressore

Illuminazione

- LED superiore di serie
- LED verticali e sui ripiani optional

Fianchi

- Panoramici con vetro temperato
- Specchio
- Ciechi

Interno

- Acciaio inox lucido o satinato
- Acciaio verniciato

Ripiani

- 5 (H205)
- Illuminazione optional

Sistema di chiusura

Porte in vetro camera

Basamento

4 piedini regolabili
ruote optional

Installation

Plug-in

Temperature range

0 / +2 °C

Refrigerant

R290

Refrigeration

Ventilated
Power Unit

Product class

M0

Climatic class

3

Defrost

Off cycle

Lighting

- LED lighting on canopy
- Vertical and undershelf LED lighting optional

Side Panels

- Panoramic with safety glass
- Mirrored
- Blind

Inside

- Polished or satin stainless steel
- Painted steel

Shelves

- 5 (H205)
- Lighting optional

Closing system

Double glass doors

Base

4 adjustable feet
wheels optional



Colori disponibili

Available colours

Interno

Inside



RAL

Acciaio inox lucido /
Polished stainless steel

Acciaio inox satinato /
Brushed stainless steel

Esterno

Outside



RAL

Acciaio inox lucido /
Polished stainless steel

Acciaio inox satinato /
Brushed stainless steel

Fianchi

Side panels



RAL

Acciaio inox lucido /
Polished stainless steel

Acciaio inox satinato /
Brushed stainless steel

POWER
UNIT



Supernova Power Unit

	94 2P TN RV	125 2P TN RV	188 4P TN RV	250 4P TN RV
Dimensioni esterne (LxPxH) External dimensions (LxDxH)	993x780x2055 mm 993x780x2124 mm	1300x780x2055 mm 1300x780x2124 mm	1935x780x2055 mm 1935x780x2124 mm	2550x780x2055 mm 2550x780x2124 mm
Capacità (lorda/netta) Capacity (gross/net)	831/555 lt	1104/737 lt	1663/1111 lt	2207/1475 lt
Peso (netto) Weight (net)	285 kg	320 kg	440 kg	520 kg
Area espositiva Total Display Area (TDA)	2,56 m ²	3,02 m ²	3,85 m ²	4,76 m ²
Refrigerazione Refrigeration	Ventilata Ventilated			
Refrigerante Refrigerant	R290			
Sbrinamento Defrost	Fermata compressore Off cycle			
Temperatura prodotto Product temperature	-1 / +4 °C			
Classe climatica Climate class	3			
Condizioni ambientali Operating conditions	25°C / 60% RH			
Classe energetica Energy class	A	A	B	B

DATI ELETTRICI - Dati tecnici riferiti a modelli con unità a bordo con unità condensatrice plug-in R290, illuminazione LED superiore 3000K, ripiani non illuminati, spalle panoramiche, chiusura con porte in vetro camera.

ELECTRICAL DATA - Technical sheet about models with air-cooled plug-in unit R290, LED canopy lighting 3000K, non-illuminated shelves, panoramic end side panels, closing system double glass door.

	1 Power unit		2 Power unit	
Compressore (q.tà - tipologia) Compressor (q.ty - type)	230 V / 1 Ph / 50 Hz			
Alimentazione Power supply	230 V / 1 Ph / 50 Hz			
Assorbimento elettrico (regime) Electrical input (nominal)	410 W / 2 A	430 W / 2 A	800 W / 4 A	860 W / 4 A
Assorbimento elettrico (sbrinamento) Electrical input (defrost)	35 W / 0,1 A	40 W / 0,3 A	70 W / 0,7 A	80 W / 0,6 A

ALLESTIMENTO SETUP

Dimensioni ripiani (LxP) Dimensions ripiani (LxP)	937 x 450 mm	1245 x 450 mm	1874 x 450 mm	2490 x 450 mm
---	--------------	---------------	---------------	---------------

